


Dual Inline Package 4pin type
of 400V load voltage

PHOTO DMOS RELAY AY40 (H)(A)

1 From A




FEATURE

1. Continuous load current: Max. 130mA.
2. Load on resistance: Typ. 20Ω.
3. Loading voltage 400V DC or AC peak.
4. Off-state leakage current: 1μA.

TYPICAL APPLICATIONS

- Measurement and test equipment
- Telecommunications
- Security equipment
- Industrial machinery and equipment



1. LED Anode
2. LED Cathode
3. MOSFET Drain
4. MOSFET Drain

Absolute maximum ratings (Ambient temperature 25 °C)

Item		Symbol	Value	Units	Not
Input	Continuous LED current	I_F	50	mA	
	Peak LED current	I_{FP}	1000	mA	f=100Hz, DC 1%
	LED reverse voltage	V_R	5	V	
	Input power dissipation	P_{in}	75	mW	
Output	Load voltage	V_L	400	V	DC or AC peak
	Load current	I_L	130	mA	
	Peak load current	I_{peak}	600	mA	100ms(1 pulse)
	Output power dissipation	P_{out}	300	mW	
Total power dissipation		P_T	350	mW	
I/O isolation voltage		V_{iso}	3750	Vrms	RH 60, 1min
I/O isolation voltage(H)			5000	Vrms	RH 60, 1min
Operating temperature		T_{opr}	-40o +85	°C	
Storage temperature		T_{stg}	-40 to +100	°C	
Soldering temperature		T_{sol}	260	°C	10sec max.



RAPIDTEK
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay

Electrical specifications (Ambient temperature 25 °C)							
Item		Symbol	Min.	Typ.	Max.	Units	Condition
Input	LED forward voltage	V_F		1.2	1.5	V	$I_F=10\text{mA}$
	Operating LED current	I_{Fon}		0.5	5.0	mA	
	Recover LED current	I_{Foff}	0.1	0.35		mA	
	Recover LED voltage	V_{Foff}	0.5			V	
Output	On resistance	R_{on}		20	30	Ω	$I_F=10\text{mA}, I_L=100\text{mA}$
	Off-state leakage current	I_{leak}			1.0	μA	$V_L=\text{Rating}$
	Output capacitance	C_{out}		50		pF	$V_L=0\text{V}, f=1\text{MHz}$
Transmission	Turn on time	T_{on}		0.3	1.0	ms	$I_F=10\text{mA}, I_L=100\text{mA}$
	Turn off time	T_{off}		0.05	0.5	ms	
Coupled	I/O isolation resistance	$R_{I/O}$	10^9			Ω	DC 500V
	I/O capacitance	$C_{I/O}$		0.8	1.5	pF	$f=1\text{MHz}$



RAPIDTEK
PHOTO DMOD RELAY


Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY


1 Form A Photo Relay

Reference data


Load current vs. Ambient temperature




On resistance vs. Ambient temperature




Turn on time vs. Ambient temperature




Turn off time vs. Ambient temperature




LED operate current vs. Ambient temperature




LED turn off current vs. Ambient temperature




LED forward voltage vs. Ambient temperature




Voltage vs. current characteristics of output at




Off state leakage current vs. Load voltage




LED forward current vs. Turn on time



LED forward current vs. Turn off time



Applied voltage vs. Output capacitance




RAPIDTEK
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay

Taping specifications for surface mount devices



	B_0 (mm)	F_0 (mm)	W_0 (mm)
Specification	5.3 ± 0.1	7.5 ± 0.1	16 ± 0.1

Package	Part No.		Packing quantity	
	Tube packing	Tape & Reel packing	Tube	Tape & Reel
DIP4	AY40(H)	-	100pcs/1tube	-
SMD4	AY40(H)A	AY40(H)A-R1		1000 pcs

*H:Option



RAPIDTEK
PHOTO DMOD RELAY


Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay


Dimension

Recommended mounting pad



Unit:mm[inch]

Tolerance:±0.2[±0.007]



Unit:mm[inch]

Tolerance:±0.2[±0.007]

Marking

(Each photo MOS Relay shall be marked with the following information)



YY : Year, M : Monthly, W : Weeks

*H:Option



RAPIDTEK
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>